



'H' TYPE or Fabricated 4-column Type, 4-nos Hard Chrome Pillars Type Presses, Straight Sided Press and 8- Point Gib Guided Hydraulic Press

Models	Capacity (Tons)	Ram Size (mm)	Daylight (mm)	Stroke (mm)	Shut Height (mm)	Table Size (LxW) mm	Speeds (mm / sec.)			Electric Motor (H.P.)	No. of Cylinders	Working Ht. (mm)	Bottom Ejector	Slide Locking arrangement	T - Slots	Working Pr. (Bar)	Weight of m/c (approx.) Tons
							Approach	Pressing	Return								
HP - 5	5	80	300	300	-	350 x 300	20-25	5-8	30	3	1 (D/A)	700	Optional	-	T - 16	200	1
HP - 10	10	100	350	350	-	350 x 300	25-30	5-8	30	5	1 No. (D/A)	700	Optional	-	T - 16	200	1.5 to 2
HP - 15	15	120	400	400	-	400 x 300	25-30	5-8	30-40	5	1No. (D/A)	700	Optional	-	T - 16	200	1.5 to 2
HP - 20	20	125	400	400	-	400 x 300	25	5-8	30	5	1 No. (D/A)	700	Optional	-	T - 16	200	2
HP - 25	25	125	400	400	-	450 x 300	25	5-8	30	5	1No. (D/A)	700	Optional	-	T - 16	200	2.5
HP - 30	30	140	400	400	-	450 x 300	25	5-8	30	5	1No. (D/A)	700	Optional	-	T - 16	200	3
HP - 50/60	50/60	200	450	450	-	500 x 500	70	10-15	80	7.5	1 + 2	750	Optional	-	T - 16	200	4
HP - 80	80	220	500	400	100	600 x 500	70	10-15	80	7.5	1 + 2	750	Optional	-	T-20	200	4 to 5
HP - 100	100	250	600	450	150	600 x 600	80	10-15	90	7.5	1 + 2	750	Optional	-	T-20	200	5
HP - 125	125	270	700	550	150	600 x 600	80	10-15	90	10	1+2	750	Optional	-	T-22	200	5 to 6
HP - 150	150	300	700	550	150	650 x 500	80	10-15	90	15	1 + 2	750	Optional	-	T-22	200	6
HP - 200	200	350	700	500	200	800 x 600	80	10-15	90	15	1 + 2	750	Optional	Provided	T-22	200	9 to 10
HP - 250	250	400	800	550	250	800 x 600	100	15-20	110	20	1+2	750	Optional	Provided	T-22	200	10
HP - 300	300	440	800	600	200	900 x 700	100	15-20	110	25	1+2	750	Optional	Provided	T-24	200	10 to 11
HP - 350	350	470	900	600	300	900 x 00	120	15-20	130	25	1 + 2	750	Optional	Provided	T-24	200	12
HP - 400	400	510	900	600	300	1000 x 800	120	15-20	130	30	1+2	750	Optional	Provided	T-24	200	12 to 13
HP - 500	500	565	1000	700	300	1200 x 800	130	20-25	140	40	1 + 2	750	Optional	Provided	T-24	200	13 to 14
HP - 600	600	440	1000	700	300	1250 x 900	130	20-25	140	40	2 + 2	800	Optional	Provided	T-24	200	16 to 18
HP - 700	700	470	1000	700	300	1250 x 900	150	20-25	160	40	2 + 2	800	Optional	Provided	T-30	200	22 to 25
HP - 800	800	510	1000	700	300	1500 x 1000	150	20-25	160	50	2 + 2	800	Optional	Provided	T-30	200	26 to 28
HP - 900	900	530	1200	800	400	1500 x 1000	150	20-25	160	50	2 + 2	800	Optional	Provided	T-30	200	30 to 35
HP - 1000	1000	565	1200	800	400	1500 x 1200	180	20-25	200	75	2 + 2	800	Optional	Provided	T-30	200	35 to 40
HP - 1200	1200	510	1500	1000	500	2000 x 1500	180	20-25	200	75	3 + 4	800	Optional	Provided	T-30	200	45
HP - 1500	1500	565	1500	1000	500	2000 x 1500	200	30	210	100	3 + 4	800	Optional	Provided	T-30	200	50