

“C” FRAME TYPE PRESSES

TECHNICAL SPECIFICATIONS

Models	Capacity (Tons)	Piston or Ram Size (mm)	Stroke Length (mm)	Daylight (mm)	Shut Height	Table Size (LxW) mm	Approach Speed (mm/sec.)	Pressing Speed (mm/sec.)	Return Speed (mm/sec.)	Electric Motor (H.P.)	Weight of the Press (Tons)	No. of Cylinders
HCP - 5	5	80	250	300	50	350x300	20 - 25	5 to 8	30	3	1	1 No. Double Acting
HCP - 10	10	100	300	350	50	400x300	25 - 30	5 to 8	30-40	5	1.5 to 2	1 No. Double Acting
HCP - 15	15	120	300	400	100	400x300	25 - 30	5 to 8	30-40	5	2 to 2.5	1 No. Double Acting
HCP - 20	20	125	300	400	100	450x300	30	5 to 8	40	5	2.5 to 3	1 No. Double Acting
HCP - 25	25	125	300	400	100	450x300	25 - 30	5 to 8	30-40	5	3	1 No. Double Acting
HCP - 30	30	140	300	400	100	450x300	80	10 to 15	80-90	5	4	1 + 2 Nos.
HCP - 50/60	50/60	200	300	400	100	500x350	70	10 to 15	80-90	7.5	6	1 + 2 Nos.
HCP - 80	80	220	400	500	100	550x400	80	10 to 15	80-90	10	7	1 + 2 Nos.
HCP - 100	100	250	500	650	150	600x400	80	10 to 15	80-90	10	8	1 + 2 Nos.
HCP - 125	125	270	550	700	150	600x400	80	10 to 15	80-90	10	10	1 + 2 Nos.
HCP - 150	150	300	600	750	150	650x450	80	10 to 15	80-90	15	12	1 + 2 Nos.
HCP - 200	200	350	600	750	150	750x500	80	10 to 15	80-90	20	14	1 + 2 Nos.
HCP - 250	250	400	600	750	150	850x600	80	10	90	25	15	1 + 2 Nos.